

Beavertail tile roof | clamping system top-fix

Clamping system on beavertail tile roofing with modules installed in portrait





Solution for beavertail tiles

- components usable across different roof types
- module landscape installation possible with cross layer system
- only two clamps for all frame heights in blank and black anodized

product variants

- roof hook flex for lower loads or 40mm battens
- roof hoof beavertail available also as double roof hook
- rails and clamps available in blank and black anodized

Your benefits

- three-way adjustable roof hook to level out uneven roofs, for different tile strenghts and shapes
- the C-rail also acts as a cable channel
- no beavertail sheet metal tile required
- narrow tile gap and centric load distribution




Position of the bracket with beavertail tiling



Rail connector C 47 S for profile chambers



Slip guard for fixing modules



Pic Designation

 Middle and end clamp for frame heights of 30-42 mm and 43-52 mm installation-friendly thanks to click-in mechanism 	5
 C-rail • available in different strength and lengths • can be stepped on throughout installation 	Light roof hooks for narrow rafters
 End cap for optically tidy rail ends Slip guard for fixing modules mounted in landscape 	
 Roof hook three-way adjustable for perfect installations various roof hooks for low and high load situations 	
Screws	Variations of C-rail

Screws

5

- building authority-approved
- Ø 6 / 8 mm available in different lengths





novotegra GmbH

Eisenbahnstraße 150 | 72072 Tübingen | Deutschland Tel. +49 7071 98987-0, info@novotegra.com www.novotegra.com

> Subject to changes and errors excepted. Last updated: April 2021 / TP